

CS201 Controller & Siren

CS201 Lighting Controller & Electronic Siren

The Hazard Systems **CS201** siren is 200W capable, available in 12V or 24V versions, and features a control head with an integrated Public Address microphone. The **CS201** is our base model. It is a siren-only with no warning light controls, and a 3-button (+ push-to-talk) control head:

- Siren / tone scroll
- Air horn
- Cancel



Control Head / Microphone Features:

- Integrated Microphone Control Head
- Adjustable Public Address Volume
- High Quality Construction
- Rubberised 'Soft-Touch' Handpiece
- Swivel mounting cradle
- Backlit, illuminated buttons
- Easy to use, low-clutter button layout
- 1,2,3 Progressive warning level buttons
- 'Hands-Free' control mode



CS201
CONTROL HEAD

Electronic Siren Amplifier Unit Features:

- Rugged Extruded Amplifier Housing
- Specially Designed Convective Cooling Fins
- Protected against Under-Voltage, Over-Voltage, Reverse-Polarity, Supply Transients & Output Short-Circuits
- Protected against Thermal Overload
- Available for 12V or 24V vehicles
- Designed to drive one or two 11-ohm 100-Watt siren speakers
- Up to 200W siren output power, or 400W with optional slave amplifier unit
- Wide range of supported siren tones
- SOFTSTART™ siren tones
- Vehicle Horn interface (HRT)
- Dedicated Automatic Gain Control (AGC) circuit optimises Public Address clarity



SIREN AMPLIFIER

PART NUMBER	DESCRIPTION
809-015	CS201 Complete Kit 12V (comprises CS201 12V amplifier and controller, cradle, harness and instructions).
809-016	CS201 Complete Kit 24V (comprises CS201 24V amplifier and controller, cradle, harness and instructions).
809-930	CS201 12V Amplifier
809-931	CS201 24V Amplifier
809-936	Wiring Harness Kit - standard
809-937	Wiring Harness Kit - slave
809-932	CS201 Controller
809-938	Controller Cradle

For more information, contact Hazard Systems - Freecall: 1800 815 000

Telephone: (03) 6332 2444 Facsimile: (03) 6332 2490 Email: sales@hazard.com.au Internet: www.hazard.com.au